

MACtransfer® 215

PRODUCT DESCRIPTION

MACtransfer 215 consists of a latex impregnated paper stock coated on one side with a medium tack removable adhesive and is manufactured in a self-wound form.

The non adhesive coated side of the tape is printable.

Face material:

Latex impregnated paper stock.

Adhesive:

Medium tack rubber based removable pressure-sensitive adhesive.

TYPICAL USE

MACtransfer 215 is designed to assist in the protection, application and transfer of unprinted die-cut pressure-sensitive decals.

SHELF LIFE

1 year when stored at 15 to 25°C and ± 50 % relative humidity (in the original packaging).

APPLICATION METHOD

The transfer of the cut vinyl onto the Application Tape should always be performed by removing the liner from the pressure-sensitive material (i.e. with the PVC face downwards onto the working surface) and not by lifting off the Application Tape.

PHYSICAL PROPERTIES (TYPICAL VALUES)

Face Material Data, 23°C	Average values	Test method
Tensile strength (N/15mm)	40	DIN ISO 527-3
Elongation at break (%)	2.5	Machine direction

Thickness

Face film + adhesive (µm)	110	ASTM D-645
---------------------------	-----	------------

Weight

Face film + adhesive (g/m ²)	90	DIN 53452
--	----	-----------

Adhesive data, 23°C (N/25 mm)

Peel on mirror Stainless Steel 20 minutes	1.5	FTM 1 180°
Peel 24hrs on MACal 8900 PRO matt	2.2	
MACal 9800 PRO Gloss	2.9	

Important notice Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use.

All technical data are subject to change. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

Disclaimer and warranty Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>. Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.